



VALPAINT S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
E-mail: info@valpaint.it
C.F./P.IVA/R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.

www.valpaint.it • www.valpaintjungle.it

SC 00224

L50

Technical Sheet:

NAME:

L50

TYPE:

water based paint

USE:

to add in Artecò 7 already coloured and Artecò'7 Metal to obtain the metallic effect. It can be added also to any Polistof shades to have Velvet Fabric Effect with L50 or Shantung Fabric Effect always with L50.

TECHNICAL DATA

specific weight:

1.020 - 1.200 ± 30 gr/LT. at 20°C

viscosity:

===

yield:

2 X LT. 0,100 per LT. 1 of ARTECO' 7
LT. 0,500 per LT. 2,5 of ARTECO' 7
2 X LT. 0,500 per LT. 5 of ARTECO' 7
2 X LT. 0,100 per LT. 1 of ARTECO' 7 METAL
LT. 0,500 per LT. 2,5 of ARTECO' 7 METAL
LT. 0,100 per LT. 1 of POLISTOF
LT. 0,500 per LT. 5 of POLISTOF

colours:

colours from the catalogue

packaging:

LT.0,100 - LT. 0,500

DRYING TIME :

on the surface:

===

overpainting:

===

below the painting :

===

CHARACTERISTICS AND RESISTANCE:

product stable to light and resistant to washing. Available in different shades to add in Artecò 7 already coloured or in Artecò'7 Metal or in any Polistof Shades

===

PREPARATION OF THE SURFACE:

PREPARATION OF THE PRODUCT :

dilution:

ready to use.

catalization relation:

===

pot life:

===

APPLICATION:

system:

pour the product L50 in Artecò 7 already coloured or in Artecò' 7 Metal or Polistof and mix well.

coats:

===

stability:

2 years approximately in pack well closed and never opened.

NOTES:

Application temperature must be between +5°C and +30°C. Wash the tools soon after use with water and soap. Keep away from freezing.

Technical Sheet n° SC 00224 issued by the Control Quality Department:

Edition n° 4

September 2014