

NAUTILUS

Technical Sheet

NAME:

NAUTILUS

TYPE:

A water-based semi mat

USE:

water based indoor use decorations

TECHNICAL DATA

specific weight: 1.200 ± 30 gr/LT at 20°C

viscosity: 2500 cps

yield : 12 - 14 m²/LT a coating (it may vary according to the roughness, porosity and surface absorption and to the method of application)

aesthetic effect: mat

colours: colours from the catalogue

packaging: LT. 1

on the surface: 1-2 hours at 20°C

overpainting : 8-10 hours at 20° C

below the painting: 24 hours at 20°C

DRYING TIME:

CHARACTERISTICS AND RESISTANCE:

Special semi mat water based paint with a very low absorbing power. It increased working time of Mavericks allowing to create extraordinary colours and luminescent effects which characterize the product .

Nautilus has an excellent mechanics resistance towards weathering agents.

Remove old non-adhering and peeling paint then wash using a suitable soap product. Subsequently and where necessary, smooth the surface once it dries using sandpaper then apply a suitable fixative. Lastly, apply NAUTILUS and MAVERICKS

PREPARATION OF THE SURFACE:

PREPARATION OF THE PRODUCT : APPLICATION:

dilution: 10-15% with water

system: Brush or roller

coats: 1 -2

APPLICATION CYCLE:

Use a roller or brush to apply one coat of NAUTILUS to cover new, intact and smooth surfaces, preferably using criss-cross strokes.

Only after 8 hours at 20°C apply MAVERICKS.

Application temperature: between +5°C and +25°C.

Storage: close the tin tightly after use and store at a temperature between +10°C and +30°C.

Stability: approximately 2 years, if well sealed and never opened

NOTES:

Mix well before use Wash the tools soon after use with water and soap.

Technical Sheet n° SC 00252 issued by the Control Responsible Department

Edition n° 1

January 2015

page 1 of 1