

FINISH V 14

Technical Sheet

NAME:

FINISH V 14

TYPE:

acrylic transpiring protective with 'lotus flower effect'

USE

Transparent painting for interior and exterior formulated for Meteore 10 protection.

CHARACTERISTICS:

specific weight:

1.000 ± 30 gr/LT. at 25°C

viscosity:

low viscosity

yield:

8-9 m²/LT. two coats over the Venetian Plaster Effect and the Venetian Plaster with Scales Effect;

5-6 m², two coats over the Two-Coat Plaster Effect and the Brushed Plaster Effect

aesthetic effect:

mat

colours:

transparent

packaging:

LT. 1

DRYING:

on the surface:

30 min. at 20°C

over painting:

2 hours at 20°C

below the surface:

24 hours at 20°C

CHARACTERISTICS AND RESISTANCE:

Apply FINISH V 14 to protect METEORE 10 and make it more washable, but also to create the lotus effect which makes water droplets slide off the decorated surface carrying away most of the dust particles along the decorated surface maintaining durability and resistance. Finish V 14 is characterised by a good penetration in the absorbing material as Meteore 10.

PREPARATION OF THE SURFACE:

FINISH V 14 must be applied with a roller or brush in two coats, wet on wet. After applying the first coat of FINISH V 14 on a 4-5 m² surface, proceed with the second coat (using a roller or brush) taking care to thoroughly cover the entire decorated surface already treated with the first coating of product. The surface just treated must be protected from rain for at least 48 hours.

PREPARATION OF THE PRODUCT:

thinning:

ready to use

catalization relation:

== =

pot life:

== =

APPLICATION:

system:

brush- roller

number of coatings:

2

STABILITY:

2 years approx. in pack well sealed and never opened

NOTE:

The product must be kept away from cold. Application and stocking temperature must be between + 5°C and + 35°C.

Technical Sheet n° SC 00143 issued by the Control Quality Department:

Edition n° 2

December 2018