

## L50

### Technical Sheet:

**NAME:**

**L50**

**TYPE:**

water based additive with aluminium and golden effects or pigments able to overlap lights creating brightening effects

**USE:**

to add in Artecò 7 already coloured and Artecò'7 Metal to obtain the metallic effect. It can be added also to any Polistof shades to have Velvet Fabric Effect with L50 or Shantung Fabric Effect always with L50. For Mavericks a pack of L 50 of any colour chosen must be added into each Mavericks can.

**TECHNICAL DATA**

**specific weight:**

1.020 - 1.200 ± 30 gr/LT. at 20°C

**viscosity:**

===

**yield:**

2 X LT. 0,100 per LT. 1 of ARTECO' 7

LT. 0,500 per LT. 2,5 of ARTECO' 7

2 X LT. 0,500 per LT. 5 of ARTECO' 7

2 X LT. 0,100 per LT. 1 of ARTECO' 7 METAL

LT. 0,500 per LT. 2,5 of ARTECO' 7 METAL

LT. 0,100 per LT. 1 of POLISTOF

LT. 0,500 per LT. 5 of POLISTOF

LT. 0,100 per LT. 0,500 of MAVERICKS

**colours:**

colours from the catalogue

**packaging:**

LT.0,100 - LT. 0,500

**DRYING TIME :**

**on the surface:**

===

**overpainting:**

===

**below the painting :**

===

**CHARACTERISTICS AND RESISTANCE:**

product stable to light and resistant to washing. Available in different shades to add in Artecò 7 already coloured or in Artecò'7 Metal or in Mavericks or in any Polistof Shades

===

**PREPARATION OF THE SURFACE:**

**PREPARATION OF THE PRODUCT :**

**dilution:**

ready to use.

**catalization relation:**

===

**pot life:**

===

**system:**

pour the product L50 in Artecò 7 already coloured or in Artecò' 7 Metal or Polistof or Mavericks can. Mix well.

**coats:**

===

**stability:**

2 years approximately in pack well closed and never opened.

**NOTES:**

Application temperature must be between +5°C and +30°C. Wash the tools soon after use with water and soap. Keep away from freezing.

**Technical Sheet n° SC 00224 issued by the Control Quality Department:  
Edition n° 5 January 2015**