



VALPAINT S.p.A.  
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY  
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384  
C.F./P.IVA/ R.I. di AN 01108220425  
Capitale Sociale € 500.000,00 i.v.  
[www.valpaint.it](http://www.valpaint.it) E-mail: [info@valpaint.it](mailto:info@valpaint.it)

SC 00222

## ADDITIVO SILVER G 200

### Technical Sheet:

**NAME:**

**ADDITIVO SILVER G 200**

**TYPE:**

Water-based silver additive

**USE:**

To be added to Klondike to get silvery shadows

**CHARACTERISTICS:**

**specific weight:** 1.070± 30 gr/LT. a 25°C

**viscosity:** = = =

**yield:** LT. 0,100 per LT. 1 of Klondike  
LT. 0,250 per LT. 2,5 of Klondike

**aesthetic effect:** silvery reflections

**colours:** silver like

**packaging:** LT. 0,100 - LT. 0,250

**DRYING:**

**on surface:** = = =

**over painting:** = = =

**in depth:** = = =

**CHARACTERISTICS AND**

**RESISTANCE:**

product stable to light and resistant to washing . Add to Klondike silvery reflections to the paint.

**PREPARATION OF THE**

= = =

**SUPPORT:**

**PREPARATION OF THE**

**dilution:** ready to use. Add to Klondike and mix well

**PRODUCT:**

**catalization relation:** = = =

**pot life:** = = =

**APPLICATION:**

**system :** add the Additive Silver G 200 in Klondike already coloured can and mix well

**number of coating:** = = =

**NOTES:**

- Working tools must be washed carefully soon after use with water
- Storage and application temperature must be superior to +5°C and inferior +30°C.

Technical Sheet n° SC 00222 issued by the Control Responsible of Quality

Edition n° 1

December 2009