



VALPAINT S.p.A.  
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY  
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384  
E-mail: info@valpaint.it  
C.F./P.IVA/R.I. di AN 01108220425  
Capitale Sociale € 500.000,00 i.v.

www.valpaint.it

SC 00149

## POLIBRIL

### Technical Sheet:

**NAME:**

**TYPE:**

**USE:**

**TECHNICAL DATA:**

**POLIBRIL**

pearls with iridescent effects.

to be added to Polistof to get light iridescent effect

**specific weight:** 1.000 ± 30 gr/LT. at 25°C

**viscosity** = = =

**yield:** LT. 0,100 per LT. 1 of Polistof

LT. 0,500 per LT. 5 of Polistof

**aesthetic effect:** particular effects

**colours:** similar to gold

**packaging:** LT. 0,100 - LT. 0,500

**on the surface:** = = =

**overpainting** = = =

**below the surface:** = = =

light-firm product and resistant to washings. If it is added to Polistof Polibril gives some golden effects to the decorative paint.

= = =

**DRYING TIME:**

**CHARACTERISTICS AND**

**RESISTANCES:**

**PREPARATION OF THE**

**SURFACE**

**PREPARATION OF THE**

**PRODUCT:**

**dilution:** ready to use. Add to Polistof and mix it.

**catalization relation:** = = =

**pot life:** = = =

**system:** pour the Polibril in the Polistof can and mix it.

**coating numbers:** = = =

**APPLICATION:**

**NOTES:**

- Working tools should be carefully washed after use with water.
- Application Temperature and product storage should be superior to + 5°C and inferior to +30°C.

**Technical Sheet n° SC 00149 issued by the Control Quality Technician:**

**Edition n° 2**

**June 2008**