



VALPAINT S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
E-mail: info@valpaint.it
C.F./P.IVA/R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.

www.valpaint.it

SC 00223

P40

Technical Sheet:

NAME:

TYPE:

USE:

TECHNICAL DATA

DRYING TIME :

CHARACTERISTICS AND

RESISTANCE:

PREPARATION OF THE

SURFACE:

PREPARATION OF THE

PRODUCT :

APPLICATION:

P40

water based paint

to add in Artecò 7 already coloured to vary the colours of the particles and obtain the Floral effect.

specific weight: 1.020 - ± 30 gr/LT. at 20°C

viscosity: = = =

yield: LT. 0,112 (Gr. 114) per LT.1 of ARTECO' 7

LT. 0,280 for LT. 2,5 of ARTECO' 7

2 X LT. 0,280 for LT. 5 of ARTECO' 7

colours: colours from the catalogue

packaging: LT. 0,280

on the surface: = = =

overpainting: = = =

below the painting : = = =

product stable to light and resistant to washing. Available in 11 different shades to add in Artecò 7 already coloured.

= = =

dilution:

ready to use. Add to Artecò 7 and mix adequately

Catalization relation: = = =

pot life: = = =

system: pour the product P40 in Artecò 7 pack already coloured and mix well.

coats: = = =

stability: 2 years approximately in pack well closed and never opened.

NOTES:

Application temperature must be between +5°C and +30°C. Wash the tools soon after use with water and soap. Keep away from freezing.

Technical Sheet n° SC 00223 issued by the Control Quality Department:

Edition n° 2

February 2011