

## ADDENSANTE NH

### Technical Sheet

**NAME:**

**ADDENSANTE NH**

**TYPE:**

thickener for Meteore 10, Rococò Stucco Veneziano 500 alla Calce, Rococò Stucco Veneziano 800, Rococò Grassello di Calce, Rococò Stucco Veneziano 1000 Lucido Diretto.

**USE**

add to the colored products in the dark shades, especially in the letters A and B and mix well.

**CARACTERISTICS:**

**specific weight:** 1.000 ± 30 gr/LT. at 25°C

**viscosity:** = = =

**yield:** LT. 0.060 approx. for LT. 4 of colored product in shades A and B  
LT. 0.180 approx. for LT. 12 of colored product in shades A and B

(the recommended quantities are purely indicative, and may increase or decrease depending on the viscosity you want to obtain)

**aesthetic effect:** = = =

**colours:** = = =

**packaging:** LT. 0,060- LT. 0,180

**on the surface:** = = =

**over painting:** = = =

**below the surface:** = = =

**DRYING:**

Added to products coloured mentioned above it increases viscosity

**CARACTERISTICS AND RESISTANCE:**

= = = .

**PREPARATION OF THE SURFACE:**

**PREPARATION OF THE PRODUCT:**

**thinning:** ready to use

**APPLICATION:**

**system:** If the product, once thickened, is not immediately applied, the density increases over time inside the can. It is therefore advisable to use NH thickener on the same day when the product will be applied, always checking that the desired viscosity has been reached; the viscosity can in fact vary depending on several factors including temperature and humidity

**stability:** 2 years approx. in pack well sealed and never opened

**NOTE:**

- Working tools must be well washed soon after use with water
- Application and stocking temperature of the product must be between + 5°C and + 35°C.

**Technical Sheet n° SC 00282 issued by the Control Quality Department:**

**Edition n° 1**

**December 2018**