

MAVERICKS

Technical and Environmental Sheet

NAME:

MAVERICKS

TYPE:

A water-based paint for interiors, characterized by luminescent reflections and three-dimensional colour effects, evoking the motion of sea waves.

USE:

water based paint for indoor use

TECHNICAL DATA:

specific weight: 1.300 ± 30 gr/LT at 20°C

viscosity: 3.100 cps

yield : 9 - 10 m²/LT a coating (it may vary according to the roughness, porosity and surface absorption and to the method of application)

aesthetic effect: semi mat opalescent

colours: colours from the catalogue

packaging: LT. 0,500

on the surface: 1 hour at 20°C

overpainting : 3-4 hours at 20°C

below the painting: 24 hours at 20°C

DRYING TIME:

CHARACTERISTICS AND RESISTANCE:

A water-based paint for interiors, characterized by luminescent reflections and three-dimensional colour effects, evoking the motion of sea waves. Thanks to its crystal particles, it is able to create environments that are unique among their kind.

To obtain the typical nuances characterizing MAVERICKS, both containers must be supplemented with the two L50 cans each containing a different colour.

ENVIRONMENTAL PERFORMANCE:

PERFORMANCE	LEGISLATION	VALUE	LABEL
ABSENCE OF HARMFUL SUBSTANCES	-	FREE	
EMISSION RATE OF FORMALDEHYDE, X	JIS A 1902-3	X<0.005mg/m ² h F****	
VOC On product to use	2004-42 EU Directive	max 14 g/LT (UE limit 200 g/LT) A/I Cat.	

PREPARATION OF THE SURFACE:

Remove old non-adhering and peeling paint then wash using a suitable soap product. Subsequently and where necessary, smooth the surface once it dries using sandpaper then apply a suitable fixative. Lastly, apply NAUTILUS and MAVERICKS.

PREPARATION OF THE PRODUCT :

dilution: ready to use

APPLICATION:

system: brush

coats: 1

APPLICATION CYCLE:

Use a roller or brush to apply one coat of NAUTILUS to cover new, intact and smooth surfaces (2 coatings for White colour and light tones), preferably using criss-cross strokes.

Only after 8 hours at 20°C apply MAVERICKS using the appropriate Double Brush PV 102 consisting of 2 paired brushes, each of which can be wetted with a different colour without inverting them.

Apply MAVERICKS gradually over a small surface of roughly 1 - 2 m² (at a time), if the temperature ranges between 15°C and 20°C; in case of lower temperatures, a larger surface can be covered (one portion at a time). The application technique consists in applying a small amount of product with alternating brush strokes in all directions.

While the paint is still partly wet, brush over using Brush PV 103 without paint: apply criss-cross strokes and spread the crystal particles of MAVERICKS while applying pressure.

This will create the impression of sea waves with broad and jagged - but not round - waves.

As a final touch, we recommend passing over the surface with delicate criss-cross brush strokes to remove any marks left by the brush.

Application temperature: between +5°C and +25°C.

Storage: close the tin tightly after use and store at a temperature between +10°C and +30°C.

Stability: approximately 2 years, if well sealed and never opened.

NOTES:

Mix well before use. Wash the tools soon after use with water and soap.

Technical Sheet n° SC 00253 issued by the Control Responsible Department

Edition n° 2

January 2020