

ADDENSANTE NH

Technical and Environmental Data Sheet

NAME:

ADDENSANTE NH

TYPE:

thickener for structured products as Meteore 10, Rococò Stucco Veneziano 500 alla Calce, Rococò Stucco Veneziano 800, Rococò Grassello di Calce, Rococò Stucco Veneziano 1000 Lucido Diretto, Rococo' Travertino and for Valmetal

USE

add to the colored products in the dark shades, especially in the letters A and B and mix well.

CHARACTERISTICS:

specific weight: 1.000 ± 30 gr/LT. at 25°C (ISO 2811-1)
viscosity: = = =
yield: LT. 0.060 approx. for LT. 4 of colored product in shades A and B
LT. 0.180 approx. for LT. 12 of colored product in shades A and B
for Valmetal add Addendante NH as desired up to a maximum of 1,5% of the weight

aesthetic effect: = = =

colours: = = =

packaging: LT. 0,060- LT. 0,180

CHARACTERISTICS AND RESISTANCE:

Added to products coloured mentioned above it increases viscosity

ENVIRONMENTAL PERFORMANCES:

PERFORMANCES	STANDARD	VALUE	LABEL
ABSENCE OF DANGEROUS SUBSTANCES	-	FREE	
FORMALDEHYDE ISSUE RATE, X	JIS A 1902-3	X < 0.005 mg/m ² h F*****	

PREPARATION OF THE PRODUCT:

thinning: ready to use

APPLICATION:

system: If the product, once thickened, is not immediately applied, the density increases over time inside the can. It is therefore advisable to use NH thickener on the same day when the product will be applied, always checking that the desired viscosity has been reached; the viscosity can in fact vary depending on several factors including temperature and humidity

stability: 2 years approx. in pack well sealed and never opened

NOTE:

- Working tools must be well washed soon after use with water
- Application and stocking temperature of the product must be between + 5°C and + 35°C.

Technical Sheet n° SC 00282 issued by the Control Quality Department:

Edition n° 3

April 2022