

SETAVEL

Technical and Environmental Sheet

NAME:

SETAVEL

TYPE:

Matt, water-based decorative paint for interiors with a silk effect

USE:

Easy-to-apply decorative finish for interiors.





CHARACTERISTICS:

specific weight: 1,070 ± 30 g/L at 20 °C
coverage: 4-5 m²/L with two coats (may vary depending on the roughness, porosity and absorption of the surface, and on the method of application)
Aesthetic effect: matt with a silk effect
colours: as per catalogue
format: 1 L / 2.5 L / 5 L
for painting over: 3-4 hours at 20 °C
hard-dry: 24 hours at 20 °C

CHARACTERISTICS AND RESISTANCE:

SETAVEL is a water-based decorative paint for interiors, which stands out for its matt, silk-effect finish, which is soft to the touch. It gives rooms an understated, contemporary elegance by imbuing surfaces with a delicate, refined sense of movement. It is moderately washable from 15 days after application, by wiping gently with a soft, dampened sponge to avoid marks or discolouration. Upon complete hardening, a breathable film is formed which provides good resistance against normal abrasion.

ENVIRONMENTAL PROPERTIES:

PARAMETER	STANDARD	RESULT	MARKING
INDOOR EMISSION OF POLLUTING SUBSTANCES	ISO 16000	TVOC < 1mg/m ³ Class A+	
FREEDOM FROM DANGEROUS SUBSTANCES	-	FREE	
FORMALDEHYDE EMISSION RATE, X	JIS A 1902-3	X<0.005mg/m ² h F****	
VOC in the ready-for-use product	Directive 2004/42/CE	max. 1.3 g/L (EU limit 200 g/L) Cat. A/1	

PREPARATION OF THE SUPPORT SURFACE:

Make sure that the surface is suitably firm, removing any impurities such as: dust, wax, grease, silicone, soap, and anything else that may prevent adherence. Remove any old paint if loose and flaky and wash with a suitable soap product. Afterwards, carry out any plaster filling which may be necessary and, once dry, proceed to apply the PRIMART 800 using a wool roller, paint brush or sprayer. After 6 hours at 20 °C, proceed to apply SETAVEL.

PREPARATION OF THE PRODUCT:

dilution: ready to use

APPLICATION:

system: spatula

number of coats: 2

Spatula Silk Effect: Use the PV 43 Stainless Steel Trowel to apply a first coat of SETAVEL, sending strokes of different lengths in all directions. Wait 3-4 hours at 20 °C before applying a second coat of SETAVEL in an irregular, "leopard spot" manner. After covering a surface of around 1 m², fill in the gaps with small, overlapping and criss-crossing spatula strokes

Application temperature: between +10 °C and +30 °C.

Storage: in a tightly closed tin, even after use, at temperatures between +5 °C and +30 °C.

Stability: approx. 2 years in a properly sealed, never-opened container.

NOTES: The product must be stored and applied at a temperature of between +5 °C and +30 °C. The product is damaged by frost. Tools must be washed immediately after use with soap and water.

**Technical Sheet No. SC 00333, issued by the Quality Control Manager:
Edition 2 April 2025**